

Thank you for purchasing the ~~awave~~ brand series , which is the component speaker specially designed for the non-destructive modification, They have all passed comprehensive tests to ensure its consistency and reliability.

FEATURES:

6.5 Inch 2-Way Component Speakers
Rated Power: 60W
Polypropylene Hybrid cone
4 Ohm 30mm TIL Voice coil
Qts: 0.686
BL: 4.15 T
Vas: 13.29 ltr
25mm German silk dome tweeter

PRECAUTIONS:

- Before installing the mounting hole, please confirm that the installation space is appropriate.
- To prevent noise interference, make sure that the wiring is away from the engine, high voltage conductors and other potential sources of noise.
- To prevent short circuits, make sure that the wiring avoids moving parts and sharp edges.
- Before installing this product, please make sure that you have read this installation guide carefully.

AWGM650C TECHNICAL PARAMETERS:

Specifications	Woofer	Tweeter
Power (W)	60	25
Fo (Hz)	60	1400
Nominal Impedance(Ω)	4	4
Sensitivity@ 1W/1M (dB)	88	90
Frequency Range	60Hz~8KHz	1400Hz~22KHz
Magnet	Hig-strength NdFeB	Hig-strength NdFeB
Voice Coil	30mm	25.4mm
Cone(Dome)	Polypropylene Hybrid	German silk
Mounting Depth (mm)	25	33
Mounting Diameter (mm)	178	42



AWGM650C

汽车套装喇叭说明书

CAR COMPONENT SPEAKER USER`S GUIDE

感谢您购买 **awave** 品牌系列喇叭，这是一款专门为汽车无损改装使用而设计的套装喇叭，本产品已经通过全面的测试以确保其性能的一致性和可靠性。

特性：

6.5寸二音路套装喇叭
额定功率：60W
Polypropylene Hybrid 音盆
4欧姆 30 mm TIL 音圈
Qts: 0.686
BL: 4.15T
Vas: 13.29 ltr
25mm 德国蚕丝球顶高音

注意事项：

- 在打安装孔之前，请确认安装空间是否合适。
- 为了防止噪音干扰，请确保接线远离发动机，高压导线和其他潜在的噪音来源。
- 为防止短路，请确保布线避开运动的部件和锋利的边缘。
- 在安装本产品之前，请确保您已经仔细阅读本安装指导。

AWGM650C 技术参数：

产品规格	低音	高音
功率（ W ）	60	25
最低谐振频率（ Hz ）	60	1400
阻抗（ Ω ）	4	4
灵感度（ dB ）	88	90
频率范围	60Hz～8KHz	1400Hz～22KHz
磁钢	高强性能钕铁硼	高强性能钕铁硼
音圈	30 mm	25.4mm
音盆	Polypropylene Hybrid	德国蚕丝
安装深度（ mm ）	25	33
安装直径（ mm ）	178	42



- 感谢阅读
- Thanks for your review